Bibliography

[1] David K Wagg and Mark S Nixon (2004), "On Automated Model-Based Extraction and Analysis of Gait", In proceedings of Sixth IEEE International Conference on Automatic Face and Gesture Recognition.

[2] A Kale, N Cuntoor, B Yegnanarayana, A N Rajagopolan and R Chellappa.(2003) "Gait Analysis for Human Identification." Audio and Video-Based Biometric Person Authentication Lecture Notes in Computer Science, Vol. 2688, pp. 706-714.

[3] L. Lee and W E L Grimson (2002), "Gait Analysis for Recognition and Classification", In Proceedings of Fifth IEEE International Conference on Automatic Face and Gesture Recognition, pp. 155-162.

[4] P. J. Phillips, S.Sarkar, I.Robledo, P.Grother and K. Bowyer (2002), "The Gait Identification Challenge Problem: Data Sets and Baseline Algorithm",In Proceedings of 16th International Conference on Pattern Recognition, pp. 385 - 388.

[5] Shrikrishna D Patil, Vilas M Thakare(2013), "Gait analysis and rehabilitation: a survey", International conference on advances in computer science and enginnering-CSEE-2013, pp. 171-175.

[6] Hayder A. ,Dargham J, Chekima A, and Ervin G M(2011), "Person Identification using Gait", International Journal of Computer and Electrical Engineering, Vol. 3, NO. 4, August 2011, pp.477-482

[7] Zhang Zonghua and TrojeNikolaus(2005),"View-Independent person identification from human gait" Elsevier Neurocomputing 69, pp. 250-256

[8] TheekhanontPorntep, Miguet Serge and KurutachWerasak(2012), "Gait Recognition using GEI and Pattern Transform" IEEE International Symposium on Information in Medicine and Education, pp. 936-940

[9] Dong Xu, Shuicheng Yan, D Tao, Steaphen Lin and Hong-Jiang Zhang(2007)," Marginal Fisher Analysis and Its Variants for Human Gait Recognition and Content Based Image Retrieval", IEEE transaction on Image Processing, Vol.16, No. 11, Nov 2007, pp.2811-2821.

[10] Kim Daehee, Lee S, and Paik Jooki (2009),"Active Shape-Based Gait Recognition using Infrared Images", International Journal of Signal Processing, Image processing and pattern Recognition, Vol. 2, No. 4, pp. 1-11.

[11] Modal Soumik, NandyAnup, ChakravartyPavan and Nandi G C (2012), "Gait Based Identification System using Rotation Sensor" , Journal of Emerging Trends in Computing and Information Science, Vol. 3, No. 3 , pp.395-402.

[12] Hu Ng, Tong Hau-Lee, Wooi-Haw Tan, TimthyTzen-Vun Yap, Chong, and Junaidi(2011), "Human Identification Based on Extracted Gait Features " , The Society of digital Information and wireless Communications International Conference on New Computer architecture and Their Applications, 1(2) pp. 358-370.

[13] Ming-Hsu Cheng, Meng-Fen Ho and Chung-lin Huang (2007), "Gait Analysis for Human Identification through Manifold Learning and HMM", Elsevier Journal of Pattern Recognition , Vol. 41 pp.2541-2553.

[14] Liang Wang, Huazhong, Tieniu Tan and Weiming Hu (2003), "Fusion of Static and Dynamic Body Biometrics for Gait Recognition", Proceedings of the Ninth International conference on Computer Vision, Vol. 2.

[15] Zhang Hao, Zhijing LIU and Haiyong ZHAO (2011), "Gait Modeling and Identifying Based on Dynamic Template Matching", Journal of Computational Information Systems, pp. 1155-1162.

[16] M. Pushpa Rani and G. Arumugam (2010), " An Efficient Gait Recognition System For Human Indentification Using Modified ICA", International Journal of Computer Science and information Tecnhology, Vol. 2, No. 1, pp. 55-67.

[17] Liang Wang, Weiming Hu and Tieniu Tan (2002), "A New Attempt to Gait Identification", IEEE .

[18] Goldy R and R Precila Mary (2012), "Genetic Algorithm for Self-occlusion Gait Recognition", International Journal of Advanced Research in Computer and Communication Engineering, Vol. 1, Issue 10, pp. 865-869.

[19] Wang Jin, Mary She and SaeidNahavandi (2010), "A Review of Vision-based Gait Recognition Methods for Human Identification " , IEEE Digital Image computing: Techniques and Applications, pp. 320-327

[20] Alberto Leardini, ZimiSawacha, Gabriele Paolini, StefaniaIngrosso, Roberto Nativo and Maria Grazia Benedetti (2007), “A New Anatomically Based Protocol For Gait Analysis In Children ” , Elsevier Gait and Posture Vol. 26, Issue 4, pp. 560-571.

[21] Alberto Ferrari, M G Benedetti, E Pavan, C Frigo, D Bettinelli, M Rabuffetti, P Crenna, A Leardini (2008), “Quantitative Comparison Of Five Current Protocols In Gait Analysis” Elsevier Gait and Posture, Vol. 28, Issue 2, pp. 207-216.

[22] Patrick O. Riley and D. Casey Kerrigan (1999), “Kinetics of Stiff-Legged Gait: Induced Acceleration Analysis”, IEEE Transactions on Rehabilitation Engineering, Vol. 7, No. 4, pp. 420–426.

[23] Rezaul K. Begg, MarimuthuPalaniswami and Brendan Owen (2005), “Support Vector Machines for Automated Gait Classification”, IEEE Transactions on Biomedical Engineering, Vol. 52, No. 5, pp. 828-838.

[24] Jane Courtney and A. M. de Paor (2010), “A Monocular Marker-Free Gait Measurement System”, IEEE Transactions on Neural Systems and Rehabilitation Engineering, Vol. 18, No. 4, pp. 452-460.

[25] Alexander Duschau-Wicke, Joachim von Zitzewitz, Lars Lünenburger and Robert Riener (2010), “Path Control: A Method for Patient-Cooperative Robot-Aided Gait Rehabilitation”, IEEE Transactions on Neural Systems and Rehabilitation Engineering, Vol. 18, No. 1, pp. 38-48.

[26] HoomanDejnabadi, Brigitte M. Jolles, and KamiarAminian (2008), “A New Approach for Quantitative Analysis of Inter-Joint Coordination During Gait”, IEEE Transactions on Biomedical Engineering, Vol. 55, No. 2, pp. 755-763.

[27] Robert T. Collins, Ralph Gross and Jianbo Shi (2002), “Silhouette-Based Human Identification from Body Shape and Gait”, In Proceeding of FGR '02 Proceedings of the Fifth IEEE International Conference on Automatic Face and Gesture Recognition, pp. 351-356.

[28] D. Cunado, M. S. Nixon and J. N. Carter (2003), “Automatic Extraction and Description of Human Gait Models for Recognition Purposes”, Elsevier Computer Vision and Image Understanding, Vol. 90, No. 1, pp. 1–41.

[29] C. Yam, M. S. Nixon and J. N. Carter (2002), “On the Relationship of Human Walking and Running: Automatic Person Identification by Gait”, In Proceedings of International Conference on Pattern Recognition, pp. 287-290, IEEE.

[30] D Meyer, J Posl and H Niemann (1998), “Gait Classification with HMMs for Trajectories of Body Parts Extracted by Mixture Densities”, In Proceedings of the British Machine Conference, pp. 459-468.

[31] J D Shutler, M G Grant, M S Nixon and J N Carter (2002), “On a Large Sequence-based Human Gait Database”, In Proceedings of Recent Advances in Soft Computing, pp. 66-71.